


SealBoss®

JointMaster Pro2 G3i Digital



Product Data Sheet

Two Component Joint Filler Pump



- Design G3i Industrial Grade Design with New Features
- Frame Robust, Modern & Sleek Steel Design, Stronger & Smaller Footprint
- Pumps Advanced Gear Pump System, Improved Flow Rate & Seals
- Motor Industrial, CE Grade Engineered High Tech Motor
- Digital Programmable Logic Controller with Digital Display
- Applicator Low Amp/Volt Safety Control Line to Applicator with Control Dial

Welcome to the Digital Age in Floor Repair

- Professional Use
- Two-Component
- Joint Sealer
- Highway Joint / Crack Repair
- Polyurea
- Polyurethane
- Epoxy

Inside and Outside Applications

- Warehouses
- Parking Structures
- Highway Repair
- Driveways
- Control Joints

Custom Equipped to Your Order

- Tank Volume
- Tank Material
- Manifold Cleaning Options
- Heater Band Option
- Battery & Inverter Option
- Generator Option
- 110 Volt Standard
- 220 Volt International Markets

The SealBoss® JointMaster Pro2 G3i Digital machine is for professional use. Please contact a SealBoss® representative for detailed information and to confirm that your product is suitable for use with this machine. Specific product data sheet and SDS of product to be intended for use will help you to determine the suitability. Please refer to the JointMaster Pro2 G3i Digital Manual for more information. Due to the nature of a dispensing machine like the SealBoss® JointMaster Pro2 G3i Digital, user shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any materials supplied or distributed by SealBoss® Corp. relieves the user of the obligation to read and follow the warnings and instruction for each SealBoss® Corp. product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss® Corp. warrants its products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss® Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss® Corp. does not take back or restock any used equipment. SealBoss® Corp. does not apply credit for used equipment.



SealBoss® JointMaster Pro2 G3i Digital Machines are custom equipped. Models may vary.

SealBoss® JointMaster Pro2 G3i Digital

SealBoss®

JointMaster Pro2 G3i Digital



Product Data Sheet

Two Component Joint Filler Pump

Implementing Over 10 Years of Experience and Customer Feedback

- The New JointMaster Pro2 Gen3i is Designed for a Wide Variety of Joint Filler Products
- New Pump Units, 10 Times Improved Seal Pressure Resistance
- New Programmable Digital Motor Control with Display for Consistent Product Flow & Higher Output
- Safety - Low Voltage Signal Line to Applicator
- New CE Rated Motor with Much Lower Energy Consumption - Run Longer on Battery!
- Improved, Fully Enclosed Drive Design, 3 Shaft, Reduced Friction Energy Saving Design
- New Frame Design - Smaller Footprint, Quality Fit & Finish, Better Handling, Stronger Frame
- Very High Build Quality, Sharp and Professional on the Jobsite, Enhance Your Company's Image
- Stainless Steel Tanks Standard, other Options Available
- Custom Equipped - Tank Size, Battery & Applicator Options
- International Versions, 110V, 220V, 50-60Hz

Specifications

Weight:	Basic Pump 205 lb dry. Extra equipment not included.
Height:	44" (5 gal tanks) , 47" (6 gal tanks) Width: 25", Length: 29.5"
Motor:	1/2 [hp], ~200 [lb-in], AC Gear
Pumps:	Internal rotary gear pumps
Tanks:	5 gal/ 6 gal, 14 gauge 304 stainless steel
Power:	110V 5A, 220V version available
Hoses:	3/8" x 14.5' braided, protective sleeve
Wheels:	6", swivel wheels with brakes
Control:	Extended lightweight handle, dual port manifold, digital speed control. Low voltage control line to applicator Programmable Digital Control
Viscosity:	approx. 50-4000 cps, depending on material, please call.
Flow Rate:	approx. 0.1 to over 1 gallon per minute
Ratios:	1:1 by volume ratio standard, other ratios available



SealBoss® QuickFix Joint Filler & Spall Repair Products



SealBoss® Corp. recommends SealBoss® QuickFix Products for use with the SealBoss® JointMaster Pro2 Gen3i pump systems.



Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201705

SealBoss Corp. USA info@sealboss.com

ph. 877-932-2293 intl. 1+ 714-662-4445

SealBoss® JointMaster Pro2 G3i Digital