



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION					
Product:	MEADOW-PATCH® T1		Part Number: 8211000		
Manufacturer:	W. R. MEADOWS, INC.		Address: 300 Industrial Drive Hampshire, Illinois 60140		
Telephone:	(847) 214-2100		In case of emergency, dial (800) 424-9300 (CHEMTREC)		
Revision Date:	11/6/2025				
Product Use:	Cementitious Patching/Repair Product				
SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS					
HMIS		HAZARD STATEMENTS			
 Health 	2	DANGER!			
 Flammability 	0	May cause cancer. (Category 1)			
 Reactivity 	0	May cause severe skin burns and eye damage. (Category 1B)			
 Personal Protection 		May cause an allergic skin reaction. (Category 1B)			
		Harmful if inhaled. (Category 4)			
		May cause respiratory irritation. (Category 3)			
		May cause organ damage through repeated/prolonged exposure. (Ca			
PRECAUTIONARY STATEMENTS					
Avoid direct contact.					
Avoid dust inhalation.					
Use appropriate Personal Protective Equipment.					
SECTION 3: HAZARDS COMPONENTS					
Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL (@25°C)
1. Microcrystalline Silicon Dioxide	14808-60-7	55-60	No	N/A	N/A
2. Portland Cement	65997-15-1	30-35	No	N/A	N/A
3. Hydrated Lime	1305-62-0	1-5	No	N/A	N/A
<i>N/A = Not Applicable</i>					
Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."					
SECTION 4: EMERGENCY AND FIRST AID PROCEDURES					
EYE CONTACT: Immediately flush eyes with water for fifteen (15) minutes. Seek immediate medical attention.					
SKIN CONTACT: Remove contaminated shoes/clothing. Flush affected areas with water. If irritation develops/persists, seek medical attention.					
INHALATION: Remove victim from exposure source. Treat symptomatically. If symptoms persist, seek medical attention.					
INGESTION: Do not induce vomiting. If vomiting spontaneously occurs, keep the head below the hips to prevent lung aspiration. Seek immediate medical attention.					
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.					
SECTION 5: FIRE AND EXPLOSIVES HAZARDS					
FLASHPOINT: None.					
EXTINGUISHING MEDIA: Not applicable--product will not burn.					
CHEMICAL/COMBUSTION HAZARDS: None recognized. Material will not support combustion.					
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid inhalation of dust if bags are broken. Use appropriate respiratory protection.					
SECTION 6: ACCIDENTAL RELEASE MEASURES					
SPILL OR LEAK PROCEDURES: Evacuate unauthorized personnel. Clean up using methods that will minimize dust creation or wet methods. Avoid inhalation of dust. Place in marked/non-leaking containers for disposal. Flush affected areas to remove trace residue.					
SECTION 7: HANDLING AND STORAGE					
SAFE HANDLING PROCEDURES: Avoid direct contact with this material as well as the creation of dust.					
SAFE STORAGE: Store in cool, dry location away from moisture sources.					



SAFETY DATA SHEET

Date of Preparation: 11/6/2025		Page 2 of 3		8211000				
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION								
	OSHA			ACGIH				
Chemical Name:	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Microcrystalline Silicone Dioxide	*See Below	N/E	N/E	N/E	0.025 mg/m ³	N/E	N/E	N/E
2. Portland Cement	5 mg/m ³	N/E	N/E	N/E	1 mg/m ³	N/E	N/E	N/E
3. Hydrated Lime	5 mg/m ³	N/E	N/E	N/E	5 mg/m ³	N/E	N/E	N/E
*: TWA Total Dust (30)/(%SiO ₂ + 2) mg/m ³						TWA Respiratory Fraction (10)/(%SiO ₂ + 2) mg/m ³		N/E: Not Established
ENGINEERING CONTROLS: Use equipment to keep dust levels below established exposure limits.								
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves.								
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES								
BOILING POINT: Not Applicable		VAPOR DENSITY: Not Applicable		% VOLATILE BY VOLUME: Not Applicable				
EVAPORATION RATE: Not Applicable		pH LEVEL: 10-12 (hydrated)		% VOLATILE BY WEIGHT: Not Applicable				
WEIGHT PER GALLON: Not Applicable		PRODUCT APPEARANCE: Gray Powder		VOC CONTENT: 0 g/L				
ODOR: No Odor		ODOR THRESHOLD: N/D		MELTING/FREEZING POINT: N/D				
FLASH POINT: See Section 5		FLAMMABILITY: N/D		UEL/LEL: N/D				
VAPOR PRESSURE: N/D		RELATIVE DENSITY: N/D		SOLUBILITY: N/D				
PARTITION COEFFICIENT: N/D		AUTOIGNITION TEMPERATURE: N/D		DECOMPOSITION TEMPERATURE: N/D				
VISCOSITY: N/D						N/D: Not Determined		
SECTION 10: STABILITY/REACTIVITY								
STABILITY: Stable.		HAZARDOUS POLYMERIZATION: Will not occur.						
CONDITIONS AND MATERIALS TO AVOID: When hydrated-acids, ammonium salts, aluminum metal.								
HAZARDOUS DECOMPOSITION PRODUCTS: None recognized.								
SECTION 11: TOXICOLOGICAL INFORMATION								
EYE CONTACT: Direct contact may result in severe irritation and possible chemical burns.								
SKIN CONTACT: May cause moderate skin irritation. Prolonged contact may result in chemical burns. Prolonged/repeated contact may cause sensitization reactions in susceptible individuals.								
INHALATION: Exposure may cause moderate irritation of the nose, throat, respiratory tract, and other mucous membranes. Inhalation of silica dust may result in lung disease (Silicosis).								
INGESTION: May cause mild to moderate irritation of the digestive tract. May cause stomach upset and vomiting.								
SIGNS AND SYMPTOMS: Symptoms of eye exposure include pain, burning, redness, and swelling. Symptoms of skin irritation include redness, burning, swelling, and rash. Symptoms of respiratory irritation include runny nose, shortness of breath, chest discomfort, and reduced lung function. Symptoms of gastrointestinal exposure include abdominal pain, nausea, and vomiting.								
AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.								
OTHER HEALTH EFFECTS: Silicon dioxide is listed by the IARC and NTP as being carcinogenic to humans (IARC Group 1A).								
SECTION 12: ECOLOGICAL INFORMATION								
ECOTOXICITY: N/E		DEGRADABILITY: N/E		BIOACCUMULATIVE POTENTIAL: N/E				
SOIL MOBILITY: N/E		OTHER ADVERSE EFFECTS: N/E						
SECTION 13: WASTE DISPOSAL INFORMATION								
WASTE DISPOSAL INFORMATION: Hydrated material will solidify to a non-hazardous solid. Landfill dispose.								
SECTION 14: TRANSPORTATION INFORMATION								
HAZARDOUS/NON-HAZARDOUS MATERIAL: Non-hazardous material.								
UN NUMBER: None.		HAZARD CLASS: None.		PACKING GROUP: None.				
UN PROPER SHIPPING NAME: None.								
ENVIRONMENTAL HAZARDS: None.								
BULK TRANSPORTATION INFORMATION: Not applicable; product is not shipped in bulk configuration.								
SPECIAL PRECAUTIONS: None.								
SECTION 15: REGULATORY INFORMATION								
OTHER REGULATORY CONSIDERATIONS: None.								
SECTION 16: OTHER INFORMATION								
PREPARATION DATE:		11/6/2025						
PREPARED BY:		Dave Carey						

SAFETY DATA SHEET

Date of Preparation: 11/6/2025

Page 3 of 3

8211000

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.

UNITIS
CONTRACTOR SUPPLIES