

BRICKFORM

LIQUID RELEASE

Technical Information Sheet | Nov.29.23 | Pg 1/2

PRODUCT DESCRIPTION

Brickform Liquid Release is a colorless release agent formulated and recommended for use with Brickform texture mats or concrete stamping tools. Liquid Release forms a temporary barrier that prevents imprinting tools from sticking to the concrete surface during the stamping process. It is commonly used on interior applications in place of powdered release or where final projects require topical stains or coatings.

USES

- Alternative to powdered release agents.
- Texturing process of both colored and uncolored concrete
- Interior or exterior applications
- Use with Brickform Stampable Overlays

FEATURES

- Prevents Concrete Buildup
- Decreases Friction
- Prolongs Tool Life
- Applied With Sprayer

COVERAGE RATES AND PACKAGING

- Available in 1 gal (3.785 L) & 5 gal (18.92 L) containers
- One gallon (3.785 L) of Brickform Liquid Release will release approximately 150-250 (13.93 - 23.22 m²) square feet of concrete surface.

STORAGE & SHELF LIFE

- Store in a safe place, out of direct sunlight. Keep containers tightly sealed. DO NOT allow product to freeze.
- Shelf life is approximately 12-24 months.

USE & APPLICATION

PRECAUTIONS:

Brickform strongly recommends jobsite samples or mockups with these products. Individuals who will be performing the work should test different sections of the concrete to determine suitability, coverage, coverage rates and final appearance.

- Brickform Liquid Release can only be used on the immediate area to be imprinted. If used on an extensive area at one time, it will evaporate before the concrete can realistically be textured. NEVER trowel or mix Brickform Liquid Release into the plastic, concrete surface.

PREPARATION:

Trowel and finish newly poured concrete surfaces, in preparation of the imprinting process. When the concrete has reached the plastic stage desirable for imprinting, Brickform Liquid Release should be used between the texture mats and the concrete, to prevent sticking and concrete buildup.

APPLICATION:

Apply in temperatures between 55° and 80°F (12.8°C and 26.7°C). Using a pump-type sprayer, liberally apply a mist of Brickform Liquid Release on the texturing mats AND on the concrete surface but only on the area where you are going to place the next few mats. Apply over an area of approximately 10 or 15 square feet (.929 - 1.39 m²), to avoid evaporation before the mat placements are made, especially on dry, windy days. NEVER trowel or mix Brickform Liquid Release into the plastic concrete surface. To make corrections on the still-plastic concrete, use the texturing tool or skins and press out unwanted impressions. When stamping is completed, wash off the Brickform Liquid Release from the texturing mats, using plain water.



CURING & SEALING

Brickform Cure & Seal or Sealers can be applied in accordance with the chosen product guidelines and surface preparation. Once sealed, protect the surface from foot traffic for 24 hours and vehicular traffic for 5 days.

MAINTENANCE

The sealed surface should be inspected periodically for areas of thin or traffic-worn sealer. Brickform recommends the reapplication of sealer as needed. If traces of efflorescence are present, this should first be eliminated with a gentle cleaner such as Brickform E-Etch. Brickform recommends the application of Brickform Premium Acrylic Floor Finish as a sacrificial coating on interior surfaces, reapply as needed, according to the appropriate Technical Information Sheet.

RECOMMENDED TOOLS & CLEAN UP

- Solvent Sprayer
- Texturing Tools

CLEAN UP:

Clean spills, tools, and sprayers with soap and water.

COMPLEMENTARY PRODUCTS

- Neutra Clean – Cleaning and neutralizing agent
- E-Etch – Cleaning and etching agent, efflorescence removal
- Antique-it
- Stains
- Sealers

BRICKFORM

LIQUID RELEASE

Technical Information Sheet | Nov.29.23 | Pg 2/2

SAFETY & PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Do not breathe vapors or mist. Use only with adequate ventilation and use a respirator when levels are above applicable limits. Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

Liquid Release

Item Number:

1-Gallon (3.785 L) LR-1

5-Gallons (18.92 L) LR-5

For more information go to:

solomoncolors.com or Brickform.com



INFORMATION