



## PRODUCT DATA SHEET

# Speed Dowel

### Slip Dowel Installation System

#### PRODUCT DESCRIPTION

Speed Dowel is the pioneering slip dowel installation system that ensures proper dowel alignment for positive load transfer in slab-on-ground concrete joints. Speed Dowel® provides a practical dowel alignment method for transferring loads across, and managing stresses within concrete slab-on-ground joints.

#### USES

- Warehouse/Distribution Centers
- Big Box Stores
- Manufacturing Facilities
- Commercial/Industrial Complexes
- Entertainment Centers
- Recreational Complexes
- Parking Facilities
- Airports

#### CHARACTERISTICS / ADVANTAGES

- Reduced installation time vs. conventional doweling method
- Eliminates need for greasing dowel
- Ensures proper dowel alignment

#### PRODUCT INFORMATION

<b>Chemical Base</b>	100% polypropylene
<b>Packaging</b>	Packaged 25 ea. per bag
<b>Shelf Life</b>	5 Years
<b>Storage Conditions</b>	Store in original packaging in cool, dry, warehouse conditions.
<b>Thickness</b>	<b>Speed Dowel Sleeve:</b> 0.125" <b>Speed Load Sleeve:</b> 0.075"
<b>Mass per Unit Area</b>	.088-0.92 g/cc
<b>Compression Resistance</b>	5,500-8,000 PSI (ASTM D-695)
<b>System Structure</b>	Excellent

Product Data Sheet  
Speed Dowel  
September 2019, Version 01.01  
020703830200000008

**APPLICATION INSTRUCTIONS**

**APPLICATION METHOD / TOOLS**

Attach base to edge form and tap on Speed Dowel® sleeve. Make first placement of concrete Strip form and insert ungreased dowel into Speed Dowel® sleeve.

**BASIS OF PRODUCT DATA**

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

**OTHER RESTRICTIONS**

See Legal Disclaimer.

**ENVIRONMENTAL, HEALTH AND SAFETY**

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

**LEGAL DISCLAIMER**

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**  
 201 Polito Avenue  
 Lyndhurst, NJ 07071  
 Phone: +1-800-933-7452  
 Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Mexicana S.A. de C.V.**  
 Carretera Libre Celaya Km. 8.5  
 Fracc. Industrial Balvanera  
 Corregidora, Queretaro  
 C.P. 76920  
 Phone: 52 442 2385800  
 Fax: 52 442 2250537



**Product Data Sheet**  
 Speed Dowel  
 September 2019, Version 01.01  
 020703830200000008

SpeedDowel-en-US-(09-2019)-1-1.pdf

